

# DTM185+ART320

**Fully automatic tyre changer with assist arm**

The addition of the Dunlop Assist Arm (ART320) to the DTM185 gives the professional tyre shop the facility to make easy work of changing low profile tyres

## **DTM185 Features**

Maximum wheel diameter 1200mm inclusive of tyre  
Capacity from: 10"-20" wheels clamped on the outside  
12"-23" clamped on the inside  
Tilt column action

## **DTM185 Standard fittings include**

Air filter, regulator, oiler  
Tyre inflator with pressure gauge  
Plastic protection for demount head and jaws

## **DTM185 Accessories included**

Tyre lever  
Soap bucket

## **Technical data**

Operating pressure 8-10 bar (116-145 psi)  
Dimensions (Packed) 1370x950x780mm  
Single phase only  
Weight 331kg  
CE approved



Distributed by

# DTM195

## Racing automatic tyre changer

### Features

- Suitable for low profile and run flat tyres
- Racing automatic tyre machine up to 24" alloy wheels
- Double assist arm and roller
- Bead jet blaster inflation
- Two position bead breaker
- 13" – 24" wheels clamped on outside of rim
- 15" – 28" wheels clamped on inside of rim
- Maximum wheel diameter 1200mm inclusive of tyre
- Maximum wheel width 3" – 15"
- Plastic inserts in foot help protect alloy rims
- Plastic protection for demount head and jaws

### Technical data

- Operating pressure 8-10 bar (116-145 psi)
- Dimensions (Packed) 1440x900x1830mm
- 3 phase only
- Weight 430kg
- CE approved



Distributed by